


ONE-TOUCH FITTINGS

> METRIC SYSTEM

PWT male Y




MODEL	ØD	T (Thread)	L	E	A	B	H	ØP	d	ORIFICE
PWT 04-01	4	PT1/8	38.8	22.1	8	15	10	11	6.5	2.5
PWT 04-02	4	PT1/4	41.8	22.1	10	15	14	11	8.7	2.5
PWT 04-03	4	PT3/8	43.1	22.1	11	15	17	11	11.7	2.5
PWT 04-M5	4	M5×P0.8	35.6	22.1	4	15	10	11	2.5	2.5
PWT 04-M6	4	M6×P1.0	36.1	22.1	5	15	10	11	2.5	2.5
PWT 06-01	6	PT1/8	40.1	26	8	15	12	13	6.5	2.5
PWT 06-02	6	PT1/4	43	26	10	15	14	13	8.5	4
PWT 06-03	6	PT3/8	44.3	26	11	15	17	13	11.2	4
PWT 06-04	6	PT1/2	47.8	26	14	15	21	13	14	4.5
PWT 06-M5	6	M5×P0.8	37.3	26	4	15	12	13	2.5	2.5
PWT 06-M6	6	M6×P1.0	37.8	26	5	15	12	13	2.5	2.5
PWT 08-01	8	PT1/8	46.3	29.8	8	18	14	14.4	6.8	4
PWT 08-02	8	PT1/4	48.3	29.8	10	18	14	14.4	8.2	4
PWT 08-03	8	PT3/8	49.6	29.8	11	18	17	14.4	11.9	4
PWT 08-04	8	PT1/2	53.1	29.8	14	18	21	14.4	13.9	4
PWT 10-01	10	PT1/8	55	36.8	8	22	17	18.4	6.5	6.5
PWT 10-02	10	PT1/4	57	36.8	10	22	17	18.4	8.3	6.5
PWT 10-03	10	PT3/4	58	36.8	11	22	17	18.4	11.7	6.5
PWT 10-04	10	PT1/2	61.5	36.8	14	22	21	18.4	14.3	7.5
PWT 12-01	12	PT1/8	58	42.4	8	22	19	21	6.5	6.5
PWT 12-02	12	PT1/4	60	42.4	10	22	19	21	8	6.5
PWT 12-03	12	PT3/8	62	42.4	11	22	19	21	11.5	6.5
PWT 12-04	12	PT1/2	64.5	42.4	14	22	21	21	14	7.5

ONE-TOUCH FITTINGS

> INCH SYSTEM

PWT male Y




MODEL	ØD	ØP	T (Thread)	L	E	A	B	H	ORIFICE
PWT 5/32-UNF	5/32	11	UNF10/32	38.8	21.1	3.6	15	7/16	2.5
PWT 5/32-N01	5/32	11	NPT1/8	41.7	21.1	8.5	15	7/16	3
PWT 5/32-N02	5/32	11	NPT1/4	44.7	21.1	10.5	15	9/16	3
PWT 3/16-UNF	3/16	13	UNF10/32	41.8	26	3.6	15	7/16	3
PWT 3/16-N01	3/16	13	NPT1/8	45.4	26	8.5	15	7/16	3
PWT 3/16-N02	3/16	13	NPT1/4	48.4	26	10.5	15	9/16	3
PWT 3/16-N03	3/16	13	NPT3/8	49.4	26	11.5	15	11/16	3
PWT 1/4-UNF	1/4	13	UNF10/32	45.8	26	3.6	15	1/2	2.5
PWT 1/4-N01	1/4	13	NPT1/8	47.7	26	8.5	15	1/2	4.5
PWT 1/4-N02	1/4	13	NPT1/4	50.4	26	10.5	15	9/16	4.5
PWT 1/4-N03	1/4	13	NPT3/8	51.4	26	11.5	15	11/16	4.5
PWT 5/16-N01	5/16	14.4	NPT1/8	47.0	29.8	8.5	18	9/16	6
PWT 5/16-N02	5/16	14.4	NPT1/4	49.0	29.8	10.5	18	9/16	6
PWT 5/16-N03	5/16	14.4	NPT3/8	50.0	29.8	11.5	18	11/16	6
PWT 5/16-N04	5/16	14.4	NPT1/2	53.0	29.8	14.5	18	7/8	6
PWT 3/8-N01	3/8	18.4	NPT1/8	52.7	36.8	8.5	22	11/16	5
PWT 3/8-N02	3/8	18.4	NPT1/4	54.7	36.8	10.5	22	11/16	7
PWT 3/8-N03	3/8	18.4	NPT3/8	55.7	36.8	11.5	22	11/16	7
PWT 3/8-N04	3/8	18.4	NPT1/2	58.7	36.8	14.5	22	7/8	7
PWT 1/2-N02	1/2	21	NPT1/4	64.6	42.4	10.5	22	7/8	7
PWT 1/2-N03	1/2	21	NPT3/8	65.6	42.4	11.5	22	7/8	7
PWT 1/2-N04	1/2	21	NPT1/2	68.6	42.4	14.5	22	7/8	7

ONE-TOUCH FITTINGS / G TYPE

> METRIC SYSTEM, BSPP, WITH INTEGRAL O-RING SEAL

PWT male Y



MODEL	ØD	T (Thread)	L	E	A	B	H	ORIFICE
PWT 04-G01	4	G 1/8	42.6	22.1	5.5	15	14	2.5
PWT 04-G02	4	G 1/4	44.3	22.1	7.5	15	17	2.5
PWT 06-G01	6	G 1/8	44.1	26	5.5	15	14	2.5
PWT 06-G02	6	G 1/4	46.2	26	7.5	15	17	4
PWT 06-G03	6	G 3/8	47.8	26	7.5	15	20	4
PWT 08-G01	8	G 1/8	46.5	29.8	5.5	18	14	4
PWT 08-G02	8	G 1/4	48.5	29.8	7.5	18	17	4
PWT 08-G03	8	G 3/8	50.2	29.8	7.5	18	20	4
PWT 08-G04	8	G 1/2	53.5	29.8	10	18	24	4
PWT 10-G01	10	G 1/8	55.2	36.8	5.5	22	17	6.5
PWT 10-G02	10	G 1/4	57.2	36.8	7.5	22	17	6.5
PWT 10-G03	10	G 3/8	58.9	36.8	7.5	22	20	6.5
PWT 10-G04	10	G 1/2	62.2	36.8	10	22	24	7.5
PWT 12-G02	12	G 1/4	60	42.4	7.5	22	19	6.5
PWT 12-G03	12	G 3/8	61.7	42.4	7.5	22	20	6.5
PWT 12-G04	12	G 1/2	65	42.4	10	22	24	7.5