


ONE-TOUCH FITTINGS

> METRIC SYSTEM

PST male run tee




MODEL	ØD	T (Thread)	L	E	A	B	H	ØP	d	ORIFICE
PST 04-01	4	PT1/8	38.8	24	8	15	10	11	6.5	2.5
PST 04-02	4	PT1/4	41.8	26.3	10	15	14	11	8.7	2.5
PST 04-03	4	PT3/8	43.1	28	11	15	17	11	11.7	2.5
PST 04-M5	4	M5×P0.8	35.6	24	4	15	10	11	2.5	2.5
PST 04-M6	4	M6×P1.0	36.1	24	5	15	10	11	2.5	2.5
PST 06-01	6	PT1/8	40.1	25.2	8	15	12	13	6.5	2.5
PST 06-02	6	PT1/4	43	26.9	10	15	14	13	8.5	4
PST 06-03	6	PT3/8	44.3	28.6	11	15	17	13	11.2	4
PST 06-04	6	PT1/2	47.8	30.9	14	15	21	13	14	4.5
PST 06-M5	6	M5×P0.8	37.3	25.2	4	15	12	13	2.5	2.5
PST 06-M6	6	M6×P1.0	37.8	25.2	5	15	12	13	2.5	2.5
PST 08-01	8	PT1/8	46.3	30.5	8	18	14	14.4	6.8	4
PST 08-02	8	PT1/4	48.3	30.5	10	18	14	14.4	8.2	4
PST 08-03	8	PT3/8	49.6	32.2	11	18	17	14.4	11.9	4
PST 08-04	8	PT1/2	53.1	34.5	14	18	21	14.4	13.9	4
PST 10-01	10	PT1/8	55	37.4	8	22	17	18.4	6.5	6.5
PST 10-02	10	PT1/4	57	37.4	10	22	17	18.4	8.3	6.5
PST 10-03	10	PT3/4	58	37.4	11	22	17	18.4	11.7	6.5
PST 10-04	10	PT1/2	61.5	39.7	14	22	21	18.4	14.3	7.5
PST 12-01	12	PT1/8	58	40.4	8	22	19	21	6.5	6.5
PST 12-02	12	PT1/4	60	40.4	10	22	19	21	8	6.5
PST 12-03	12	PT3/8	62	40.4	11	22	19	21	11.5	6.5
PST 12-04	12	PT1/2	64.5	41.5	14	22	21	21	14	6.5

ONE-TOUCH FITTINGS

> INCH SYSTEM

PST male run tee




MODEL	ØD	ØP	T (Thread)	L	E	A	B	H	ORIFICE
PST 5/32-UNF	5/32	11	UNF10/32	42.1	25.0	3.6	15	7/16	2.5
PST 5/32-N01	5/32	11	NPT1/8	45.7	25.0	8.5	15	7/16	3
PST 5/32-N02	5/32	11	NPT1/4	48.7	25.0	10.5	15	9/16	3
PST 3/16-UNF	3/16	13	UNF10/32	41.5	25.1	3.6	15	7/16	3
PST 3/16-N01	3/16	13	NPT1/8	45.1	25.1	8.5	15	7/16	3
PST 3/16-N02	3/16	13	NPT1/4	48.1	25.1	10.5	15	9/16	3
PST 3/16-N03	3/16	13	NPT3/8	49.1	25.1	11.5	15	11/16	3
PST 1/4-UNF	1/4	13	UNF10/32	47.4	28.0	3.6	15	1/2	2.5
PST 1/4-N01	1/4	13	NPT1/8	49.3	28.0	8.5	15	1/2	4.5
PST 1/4-N02	1/4	13	NPT1/4	52.0	28.0	10.5	15	9/16	4.5
PST 1/4-N03	1/4	13	NPT3/8	53.0	28.0	11.5	15	11/16	4.5
PST 5/16-N01	5/16	14.4	NPT1/8	53.7	30.9	8.5	18	9/16	6
PST 5/16-N02	5/16	14.4	NPT1/4	55.7	30.9	10.5	18	9/16	6
PST 5/16-N03	5/16	14.4	NPT3/8	56.7	30.9	11.5	18	11/16	6
PST 5/16-N04	5/16	14.4	NPT1/2	59.7	30.9	14.5	18	7/8	6
PST 3/8-N01	3/8	18.4	NPT1/8	63.3	34.7	8.5	22	11/16	5
PST 3/8-N02	3/8	18.4	NPT1/4	65.3	34.7	10.5	22	11/16	7
PST 3/8-N03	3/8	18.4	NPT3/8	66.3	34.7	11.5	22	11/16	7
PST 3/8-N04	3/8	18.4	NPT1/2	69.3	34.7	14.5	22	7/8	7
PST 1/2-N02	1/2	21	NPT1/4	57.3	40.8	10.5	22	3/4	8
PST 1/2-N03	1/2	21	NPT3/8	58.3	40.8	11.5	22	3/4	10
PST 1/2-N04	1/2	21	NPT1/2	61.3	40.8	14.5	22	7/8	10

ONE-TOUCH FITTINGS / G TYPE

> METRIC SYSTEM, BSPP, WITH INTEGRAL O-RING SEAL

PST male branch tee



MODEL	ØD	T (Thread)	L	E	A	B	H	ORIFICE
PST 04-G01	4	G 1/8	43.5	26.3	5.5	15	14	2.5
PST 04-G02	4	G 1/4	45.6	28	7.5	15	17	2.5
PST 06-G01	6	G 1/8	45	26.9	5.5	15	14	2.5
PST 06-G02	6	G 1/4	47.3	28.6	7.5	15	17	4
PST 06-G03	6	G 3/8	48.6	30.3	7.5	15	20	4
PST 08-G01	8	G 1/8	50.6	30.5	5.5	18	14	4
PST 08-G02	8	G 1/4	53.7	32.2	7.5	18	17	4
PST 08-G03	8	G 3/8	55	33.9	7.5	18	20	6
PST 08-G04	8	G 1/2	57.7	36.2	10	18	24	6
PST 10-G01	10	G 1/8	61	37.4	5.5	22	17	6
PST 10-G02	10	G 1/4	64.3	37.4	7.5	22	17	6.5
PST 10-G03	10	G 3/8	66.2	39.1	7.5	22	20	6.5
PST 10-G04	10	G 1/2	68.8	41.4	10	22	24	7.5
PST 12-G02	12	G 1/4	65.2	40.4	7.5	22	19	6.5
PST 12-G03	12	G 3/8	67.8	40.9	7.5	22	20	7
PST 12-G04	12	G 1/2	70.8	43.2	10	22	24	7.5