





## DIMENSIONS



## MODEL 7501A ACCELEROMETER

### SPECIFICATIONS

- +260°C Charge Output Accelerometer
- 5.6pC/g output, 15kHz Bandwidth
- Hermetically Sealed
- Miniature, Lightweight (2.1gm)

The Model 7501A is a miniature piezoelectric charge mode accelerometer with an operating temperature range to +260°C. The accelerometer is designed for high frequency vibration and shock measurements and offers a wide bandwidth to >10kHz with 5.6pC/g nominal output. The model 7501A features a hermetically sealed titanium housing and the popular through hole mount configuration.

### FEATURES

- 73°C to +260°C Operating Range
- Wide bandwidth up to >10kHz
- Titanium Housing
- Annular Shear Mode
- Isolated Mounting Surface
- Through Hole Mount

### APPLICATIONS

- Vibration & Shock Monitoring
- High Temp Applications
- Flight Testing
- High Frequency Applications
- Gearbox Vibration Monitoring

**PERFORMANCE SPECIFICATIONS**

All values are typical at +24°C, 80Hz unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.



<b>Parameters</b>		
<b>DYNAMIC</b>		<b>Notes</b>
Sensitivity (pC/g)	5.6	Typical
Sensitivity (pC/g)	4.0	Minimum
Frequency Response (Hz) <sup>2</sup>	1-8000	±10%
Frequency Response (Hz) <sup>2</sup>	0.5-10000	±2dB
Natural Frequency (Hz)	46000	
Non-Linearity (%FSO)	±1/1000g	
Transverse Sensitivity (%)	<5	
Dynamic Range (g) <sup>1</sup>	±4000	
Shock Limit (g)	10000	
<b>ELECTRICAL</b>		
Capacitance (pF)	560	Nominal
Insulation Resistance (MΩ)	>100	@100Vdc
Ground Isolation	Isolated from Mounting Surface	
<b>ENVIRONMENTAL</b>		
Temperature Response (%)	See Typical Temperature Response Curve	
Operating Temperature (°C)	-73 to +260	
Storage Temperature (°C)	-73 to +260	
Humidity	Hermetically Sealed	
<b>PHYSICAL</b>		
Sensing Element	Ceramic (shear mode)	
Case Material	Titanium	
Electrical Connector	M3 Coaxial Receptacle	
Weight (grams)	2.1	
Mounting	Through Hole (#2 insulated cap screw)	
Mounting Torque	5 lb-in (0.6 N-m)	

<sup>1</sup> Operating range over which the accelerometer meets the linearity specifications

<sup>2</sup> Low-end response of the accelerometer is a function of its associated electronics.

<b>Calibration supplied:</b>	CS-FREQ-0100	NIST Traceable Amplitude Calibration from 20Hz to ±2dB Frequency Response Limit
<b>Supplied accessories:</b>	AC-A03230	1x #2-56 Insulated Mounting Screw Assembly (3/8 inch length)
<b>Optional accessories:</b>	321-XXX	Low Noise Cable Assembly, M3 to 10-32 (XXX designates length in inches, 10ft standard)
	130	In-Line Charge Converter
	161A	4-Channel PE & IEPE Signal Conditioner
	AC-A04018	Triaxial Mounting Block

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.



**ORDERING INFORMATION**

PART NUMBERING    Model Number

7501A

**NORTH AMERICA**

Measurement Specialties, Inc.,  
a TE Connectivity Company  
1000 Lucas Way  
Hampton, VA 23666  
Sales and Customer Service  
Tel: +1-800-745-8008 or  
+1-757-766-1500  
Fax: +1-757-766-4297  
t&m@meas-spec.com

**EUROPE**

MEAS France SAS  
a TE Connectivity Company  
26 Rue des Dames  
F78340 Les Clayes-sous-Bois  
France  
Sales and Customer Service  
Tel: +33 (0) 1 79 33 00  
Fax: +33(0)1 34 81 03 59  
t&m@meas-spec.com

**ASIA**

Measurement Specialties (China), Ltd.,  
a TE Connectivity Company  
No. 26 Langshan Road  
Shenzhen High-Tech Park (North)  
Nanshan District, Shenzhen 518057  
China  
Sales and Customer Service  
Tel: +86 755 3330 5088  
Fax: +86 755 3330 5099  
t&m@meas-spec.com

**TE.com/sensorsolutions**

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.